

# Revolutionary "Three Step" Terrazzo Resurfacing & Polishing Procedures

## Step 1 & 2 Scratch Removal Discs (SRD's):

Thoroughly strip the floor to completely remove surface coatings.

Hone the terrazzo floor with the 120 grit SRD's mounted to a white pad, using the male-to-male velcro kit. Honing time 20-30 seconds per square feet with water.

Hone the terrazzo floor with the "Peach" color SRD's mounted to a white pad, using the male-to-male velcro kit. Repeating the same process in step one.

Honing time is 20-30 seconds per square feet. Work an area of 16-20 square feet at a time. Keep surface wet.

Vacuum the slurry and rinse with Neutral Stone Cleaner.



## Wet Polishing using "Stone Polish Paste" for Terrazzo Floors

### Prior to polishing "Thoroughly hone the floor with SRD's"

Protect surfaces that should not get wet. Work 20 sq. ft. at a time.

Polishing Procedures:

1. Thoroughly mix compound in the pail with a small scoop (1-2 ounce).
2. Apply 1 scoop to the floor in a circle, matching the diameter of the pad being used. Add 2-3 ounces of clean cool water to the compound.



Parish Maintenance Supply  
114 Palmetto St.  
315-433-9031

Syracuse NY 13206  
www.parish-Supply.com  
315-433-9840 fax

Using a "Natural Fiber" polish pad and a 175 rpm floor machine quickly make one pass over an area of 20 sq. ft.

Continue to buff the compound for 15-30 seconds per sq. ft., working the machine in a crosshatch pattern. Keep the compound wet at all times, do not allow floor to dry.

If the slurry becomes too dry add small amounts of water as needed.



Use a high quality wet vacuum with a squeegee tool, remove the slurry residue.

Once all the wet slurry has been completely vacuumed, damp mop the floor surface with the Neutral Stone Floor Cleaner at a ratio of 2 ounces per gallon of water.



### Repeat application if higher gloss is desired

#### Protect with **Stone Impregnating Sealer**

Impregnator H2O sealer is designed for the protection of all medium to dense porous stone surfaces.



#### Clean daily with **Neutral Stone Cleaner**

A Chelate-free cleaner, is the ideal neutral stone floor cleaner for all natural stone floors For daily cleaning dilute 1:64



#### Maintain gloss with **Twister Floor Pads**

Use the Twister floor pads to clean and polish your floors on a regular basis. Replace your ordinary pads with Twister System to maintain that High Gloss Shine.



Parish Maintenance Supply  
114 Palmetto St.  
315-433-9031

Syracuse NY 13206  
www.parish-Supply.com  
315-433-9840 fax